

**Customer Information For LCD****1. LCD OUTLINE DIMESION :**

Length : \_\_\_\_\_ mm

Width : \_\_\_\_\_ mm

Front Glass Thickness : \_\_\_\_\_ mm

Rear Glass Thickness : \_\_\_\_\_ mm

View Area :

\_\_\_\_\_ X \_\_\_\_\_ mm

**2. CONNECTOR TYPE** Zebra Heat Seal Pin Pin Pitch \_\_\_\_\_ mm

Pin Number : \_\_\_\_\_

 Bend Pin Special Pin : \_\_\_\_\_**3. DISPLAY TYPE**A.  TN  HTN  Y-G STN  Grey STN  FSTN  BSTN  Other : \_\_\_\_\_B.  Reflective  Transflective  TransmissiveC.  Positive  Negative

D. Special Requirement : \_\_\_\_\_

**4. DRIVING METHOD :**A.  Driving Voltage : \_\_\_\_\_ VB.  Static ;  Mux : \_\_\_\_\_ Duty, \_\_\_\_\_ Bias ;C.  Frequency : \_\_\_\_\_ Hz**5. VIEW DIRECTION :** 6 O'clock  12 O'clock  3 O'clock  9 O'clock  Other : \_\_\_\_\_**6. SPECIAL REQUIRMENT FOR FRONT POLARIZER** Cutting UV Anti-glare Colour : \_\_\_\_\_ Other : \_\_\_\_\_**7. TEMPERATURE RANGE :**

A. Operating Temperature : \_\_\_\_\_ °C to \_\_\_\_\_ °C

B. Storage Temperature : \_\_\_\_\_ °C to \_\_\_\_\_ °C

**8. PRINT TYPE**A.  No PrintingB.  Printing, Position : \_\_\_\_\_ , colour : \_\_\_\_\_ .**9. PACKING REQUIREMENT : \_\_\_\_\_****10. OTHER SPECIAL REQUIREMENT : \_\_\_\_\_**

Company Name : \_\_\_\_\_ Tel : \_\_\_\_\_ Fax : \_\_\_\_\_

Linkman : \_\_\_\_\_ Quantity : \_\_\_\_\_

Items : \_\_\_\_\_